

### **Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

### **Listing of Claims:**

1. (previously presented) A circuit, this circuit being provided for a communication partner appliance that is designed for contact less communication and as a data carrier, this communication partner appliance being provided for a communication system with at least one further communication partner appliance, in which circuit a first communication mode or a second communication mode can be activated, and which circuit has the means listed below:

activators for activating the first communication mode or the second communication mode, and

reception means for receiving a carrier signal that is transmitted by the at least one further communication partner appliance, and

detectors for detecting the presence of the received carrier signal, these detectors transmitting a carrier signal present signal in the event that the carrier signal is present, and otherwise transmitting a carrier signal not-present signal as a consequence of a missing carrier signal, and

command signal recognition means for recognizing a command signal that can be transmitted with the aid of the carrier signal and for generating and transmitting, within the circuit of the communication partner appliance, a command-end signal that represents the end of the transmitted command signal, and

determination means for determining whether, after the occurrence of the command-end signal, at a given measurement point in time, the carrier signal present signal is present, with which determination means a first activation signal can be transmitted when the carrier signal present signal is present, and otherwise a second activation signal can be transmitted, with which first activation signal the circuit can be brought into the first communication mode with the aid of the activators, and with which

second activation signal the circuit can be brought into the second communication mode with the aid of the activators.

2. (previously presented) A circuit as claimed in claim 1, wherein the activators are designed to activate a passive communication mode as the first communication mode, and an active communication mode as the second communication mode, wherein in the case of the active communication mode, a power supply for the circuit is provided that is independent of the carrier signal, and in the case of the passive communication mode, a power supply for the circuit is provided that is dependent on the carrier signal.

3. (previously presented) A circuit as claimed in claim 2, wherein a battery or accumulator is provided for the independent power supply.

4. (previously presented) A communication partner appliance that is designed as a data carrier and is equipped with a circuit as claimed in claim 1.

5. (previously presented) A circuit, this circuit being provided for a communication partner appliance that is designed for contact less communication and as a communication station, this communication partner appliance being provided for a communication system with at least one further communication partner appliance in which further communication partner appliance a first communication mode or a second communication mode can be activated, this circuit containing the means listed below:

production means for producing a carrier signal, and  
transmission means for transmitting the carrier signal to the further communication partner appliance, and  
arranging means for arranging a communication mode, and  
a generator for generating at least one command signal, which command signal can be transmitted to the further communication partner appliance with the aid of the carrier signal and  
first control elements for generating and transmitting, within the circuit of the communication partner appliance, a command-end signal that represents the end of the generated command signal, and

second control elements with which second control elements after the occurrence of the command-end signal the generation and/or transmission of the carrier signal can be ended at a particular point in time.

6. (previously presented) A circuit as claimed in claim 5, wherein the arranging means are designed for the optional arrangement of an active communication mode or a passive communication mode, in which active communication mode the further communication partner appliance has a power supply that is independent of the carrier signal and in which passive communication mode the further communication partner appliance has a power supply that is dependent on the carrier signal.
7. (previously presented) A circuit as claimed in claim 5, wherein energy source recognition means are provided, these energy source recognition means being adapted to recognize an energy source for supplying power to the circuit and with which energy source recognition means an energy source recognition signal can be transmitted depending on the energy source that has been recognized, and wherein the arranging means are designed to arrange the communication mode depending on the energy source recognition signal.
8. (previously presented) A circuit as claimed in claim 5, wherein response signal detectors are provided, for detecting a response signal transmitted by the further communication partner appliance in the course of which detection a change-over signal can be generated, and wherein the arranging means are designed to automatically arrange the communication mode depending on the change-over signal that has been generated.
9. (previously presented) A circuit as claimed in claim 5, wherein influencing means are provided for influencing a signal strength of the carrier signal depending on the arranged communication mode.
10. (previously presented) A communication partner appliance that is designed as a communication station and is equipped with a circuit as claimed in claim 5.

11. (currently amended) A method for activating a first communication mode or a second communication mode of a communication partner appliance wherein the communication partner appliance is provided for a communication system with at least one further communication partner appliance, and wherein a carrier signal is transmitted by the at least one further communication partner appliance this carrier signal being received with the communication partner appliance ~~and, the method comprising:~~

~~wherein detecting a presence of the received carrier signal in the communication partner appliance detection of the presence of the received carrier signal takes place, and in the event of the carrier signal being present, transmitting a carrier signal present signal is transmitted, and otherwise transmitting a carrier signal not-present signal is transmitted as a consequence of a missing carrier signal, and~~

~~wherein recognition of recognizing a command signal that can be transmitted with the aid of the carrier signal, signal takes place, and~~

~~generation and transmission of generating and transmitting within the circuit of the communication partner appliance a command-end signal that represents the end of the transmitted command-signal signal, takes place within the circuit of the communication partner appliance, and~~

~~wherein determination is carried out to see determining whether the carrier signal present signal is present, after the occurrence of the command-end signal at a measurement point in time the carrier signal present signal is present, wherein, and~~

~~transmitting a first activation signal is transmitted when to activate the communication partner appliance into the first communication mode in response to a determination that the carrier signal present signal is present, and otherwise transmitting a second activation signal is transmitted, and wherein with the first activation signal activation of the communication partner appliance into the first communication mode is carried out, or with the second activation signal activation of to activate the communication partner appliance into the second communication mode is carried out.~~

12. (canceled)

13. (canceled)